

CAPACITIVE/VIBR./CONDUCTIVE/OPEN C.

CRSP Capacitive, conductive and vibration spare parts

Spare parts	
400A002B	TC20, 4+20mA, "C", Calibration with dip-switches, 24Vdc; Out 4+20mA
400A022B	TL31R ON-OFF Local sensibility calibration supply 24 Vdc, Relay output SPDT
400A023B	TL31R ON-OFF Local sensibility calibration supply 24 Vac, Relay output SPDT
400A024B	TL31R ON-OFF Local sensibility calibration supply 115 Vac, Relay output SPDT
400A025B	TL31R ON-OFF Local sensibility calibration supply 230 Vac, Relay output SPDT
400A026B	TC7.3R local calibration, 24Vdc, 3 relays out for 3 adjustable set-points
400A050B	TC21, 4+20mA, Calibration with dip-switches and trim, 24Vdc, "C"
400A055B	TC30, 4+20mA, 2 push-buttons calibration, 2 wires, 24Vdc
400A060B	TL41R, 2 push-buttons sensibility calibration, 85+250Vac 50Hz, relay output SPDT
400A061B	LV1 preamplifier insert for vibration probe, relay output
400A072B	TC22, 4+20mA, 2 push buttons for calibration, RS485 for SMART calibration, 24Vdc.
400A073B	TC23, 4+20mA, 2 push buttons for calibration, RS485 for SMART calibration, 24Vac.
400A074B	TC24, 4+20mA, 2 push buttons for calibration, RS485 for SMART calibration, 115Vac.
400A075B	TC25, 4+20mA, 2 push buttons for calibration, RS485 for SMART calibration, 230Vac.
400A076B	TC26, 4+20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 24Vdc
400A077B	TC27, 4+20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 24Vac
400A078B	TC28, 4+20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 115Vac
400A079B	TC29, 4+20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 230Vac
400A084B	TL41R, 2 push-buttons sensibility calibration, 24Vdc/Vac - 115Vac 50Hz, relay output SPDT
400B061B	LV1 preamplifier insert for vibration probe, static output
410A001B	Interconnection printed-board for remote version (CLT,CLS and conductive)
452A001A	Ø4mm SS316 rope, with counterweight and process connection eur 113,00 + rope price/mt
452A002A	Ø6mm SS316 rope, with counterweight and process connection eur 134,00 + rope price/mt
490A001C	PC polycarbonate loaded head connection with nr. 1 cable gland + accessories mod. "B"
490A002C	Diecast aluminum varnished head connection
490A004C	DIN A aluminum head connection
490A005C	DIN B aluminum head connection
490A007C	DIN B PA (poliammide) head connection
490A052C	PC complete housing model "F" or "L" with anticondensation filter
490B034C	PC complete housing for CLS_ remote version mod "B" with nr. 1 cable gland
490B035C	PC complete housing for CLT_ remote version mod "F" with nr. 2 cable glands
490C030C	RSL200 compact version mechanic without preamplifier insert
490S024C	TC/TL41 aluminum adapter without flange
490S025C	PC polycarbonate head (mod H) + aluminum adapter with 4 holes square flange
545A007N	CE11 plastic enclosure
546A070N	Transparent cap for PC housing "F"
546B003N	PBT loaded head connection transparent cap
715A013A	IP66 gland PG13,5 for 8-13mm cable
715A018A	M20x1,5 gland for 10-14mm cable
810A011F	Bajonet bolt
830A001X	UNDECAL plug
899F001A	UNDECAL socket + fixing spring

VPA Open Channel accessories

Accessories and spare parts	
270A010R	PVC tie rod for PB200
270B010R	PVC tie rod for PB300
270D010R	PVC tie rod for PB500
420G095B	Electronic insert for FLOWMETER
835A027R	PTU50 holder in PVC for Palmer Bowlus
835B027R	FLOWMETER holder in PVC for Palmer Bowlus